

Package: miebl (via r-universe)

May 20, 2026

Title Performance Criteria Modeler for Discrete Trial Training

Version 0.1.0

Description Provides a tool for computing probabilities and other quantities that are relevant in selecting performance criteria for discrete trial training. The main function, `miebl()`, computes Bayesian and frequentist probabilities and bounds for each of n possible performance criterion choices when attempting to determine a student's true mastery level by counting their number of successful attempts at displaying learning among n trials. The reporting function `miebl_re()` takes output from `miebl()` and prepares it into a brief report for a specific criterion. `miebl_cp()` combines 2 to 5 distributions of true mastery level given performance criterion in one plot for comparison. Ramos (2025)
<[doi:10.1007/s40617-025-01058-9](https://doi.org/10.1007/s40617-025-01058-9)>.

License GPL-3

Encoding UTF-8

Depends R (>= 2.10)

RoxygenNote 7.3.2

NeedsCompilation no

Author Mark Ramos [aut, cre, cph]

Imports graphics, stats

Maintainer Mark Ramos <mlr6219@psu.edu>

Repository <https://mlr6219-ui.r-universe.dev>

Date/Publication 2025-04-25 15:34:34 UTC

RemoteUrl <https://github.com/cran/miebl>

RemoteRef HEAD

RemoteSha 1d0a7cb57627c0dc2ae61da576d453c0f5963d1e

Contents

miebl	2
miebl_cp	3
miebl_re	3
Index	5

miebl	<i>Compute relevant probabilities and estimates for selecting performance criteria</i>
-------	--

Description

Compute relevant probabilities and estimates for selecting performance criteria

Usage

```
miebl(n, tr = 0.9, shape1 = 0.5, shape2 = shape1, a = 0.05)
```

Arguments

n	number of trials
tr	true desired mastery level (default is 90%)
shape1	shape1 parameter for beta prior (default is 0.5)
shape2	shape2 parameter for beta prior (default is shape1 which means default is Jeffreys prior)
a	significance level (default is 0.05)

Value

A list of tables

Examples

```
miebl(n=5, tr=0.8, shape1=1, a=0.10)
# Creates results for 5 trials for 80% true mastery level w/ uniform prior and 0.10 significance.
```

miebl_cp	<i>Compares posterior distributions from different reports</i>
----------	--

Description

Compares posterior distributions from different reports

Usage

```
miebl_cp(R1, R2, R3 = NULL, R4 = NULL, R5 = NULL)
```

Arguments

R1	object produced by miebl_re; start from highest performance criterion to lowest
R2	object produced by miebl_re
R3	object produced by miebl_re
R4	object produced by miebl_re
R5	object produced by miebl_re

Value

a combined plot of the posterior distributions for each performance criterion

Examples

```
#create a miebl output for default 90% desired true mastery
xx<-miebl(10)
#Uses the miebl output for miebl_re for 90% and 80% performance criterion
r1<-miebl_re(xx,mc=90)
r2<-miebl_re(xx,mc=80)
miebl_cp(r1,r2)
```

miebl_re	<i>Creates a report for a specific performance criterion from a miebl out- put</i>
----------	--

Description

Creates a report for a specific performance criterion from a miebl output

Usage

```
miebl_re(mb, X = nrow(mb) - 1, mc = 100)
```

Arguments

mb	object produced by miebl
X	Number of correct responses for the performance criterion
mc	performance criterion expressed as percent e.g. 90% performance criterion is 90

Value

a report on the performance criterion selected with respect to the true mastery level desired

Examples

```
#create a miebl output for default 90% desired true mastery
xx<-miebl(10)
#Uses the miebl output for miebl_re for 90% performance criterion
miebl_re(xx,mc=90)
```

Index

miebl, 2
miebl_cp, 3
miebl_re, 3